




SEIKO



LSW single needle series (edge trimming)

High speed, Large vertical axis hook, Compound feed and walking foot, Reverse stitch, Lockstitch machines



LSW-8BLVMF

Variety


LSW-8BLVMF

Vertical edge trimming (front), synchronized binder(*)

LSW-8BLM

Vertical edge trimming(right)

(*)Available various special binder at extra charge




LSW-8BLVMF
synchronized binder

Applications


- For sewing medium to heavy weight fabrics, leather, vinyl, synthetics and laminated and coated materials
- Designed for operation such as tape binding, edge trimming for quilt, cushion, cover and automobile-interior.

* **8BLVMF** Bedding, cover, carpet.

* **8BLM** Heavy weight materials, automobile-interior and exterior decorations with trimming works.



LSW-8BLVMF



LSW-8BLM

LSW single needle series (edge trimming)

Features

- Seaming, tape binding and trimming can be performed by one operation.
- Large vertical axis hook. (Automatic hook lubrication)
- Safety clutch prevents the hook from being damaged.

• LSW-8BLM


Sewing and Trimming can be performed by one operation



Suit for sewing and trimming simultaneous
for leather, vinyl, heavy materials,
automobile-interior, exterior decorations.


• LSW-8BLVMF

Trimming(front) and Taping can be performed by one operation.



Suit for trimming and taping simultaneous
for bedding, cover, cushion and carpet, etc.
Trimming can be made in front of needle.

Special binder can be supplied upon your request.



Specifications (LSW-□)

Variety	8BLVMF	8BLM
Number of needle		Single needle
Max. sewing speed		2,500 s.p.m.
Max. stitch length		1/4" (6.5 mm)
Clearance under presser foot	15/32" (12 mm)	
by knee		21/64" (8.5 mm)
by hand		
Needle bar stroke	1-5/16" (33.2 mm)	
Needle(standard)	MTx190 (#19) , 190R (#120)	DPx17 (#22) , 135x17 (#140)
Thread	#30 (standard)	#8 (standard)
Hook	Large vertical axis hook (2.0 times)	
Amount of lift of walking foot	1/8"-15/64" standard 5/32" (3 - 6 mm) (standard 4 mm)	
Standard binder spec (extra charge)	4-Fold Tape width 2-3/8"(60 mm)	-
Distance between seam and cutting edge	6 - 18 mm (standard 14 mm) 15/64"- 45/64" (standard 35/64")	4 , 5 , 6.5 , 8 , 10 mm (standard 8 mm) 5/16" - 25/64" (standard 5/16")
Thread take up lever		Slide type
Lubrication		Semi-automatic lubrication type
Bed size		20-25/64"x 7" (518 x 177 mm)
Bobbin size		Φ 1-9/64" (Φ 29 mm), t=31/64"(12.4mm)
Working space		10-5/32"x 3-35/64" (258 x 90 mm)
Net weight(Head only)		34Kg

NOTE: (1) Speed depends on threads, materials and type of operation

(2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan
Phone : +81-47-420-3561 (Overseas dept.)
Fax : +81-47-420-3560
E-mail : exsales@seiko-sewing.co.jp

Printed in Japan 2024. 7

<https://www.seiko-sewing.co.jp/en/>