

H-2BL-AE-1

Single needle, Large horizontal axis hook, Upper and lower feed, Lockstitch machines



H-2BL-AE-1

Variety

H-2BL-AE-1


Standard model

H-2BL-AE-1-TA

For thick thread

Applications

- For sewing medium to heavy weight materials such as fabrics, leather, vinyl, synthetics and laminated and coated products.
- Suitable for sewing such products as bags, automobile work, awnings, vinyl and leather goods etc.



Features

- Full automatic lubrication system by pump.
- Large horizontal axis hook (2.0 times).
- Automatic lubricated hook.
- Feed regulating dial stopper assures uniform stitching.
- High presser foot lift.
- Easy adjustment of forward and reverse stitch length.

Specifications

Variety		H-2BL-AE-1	H-2BL-AE-1-TA
Number of needle		Single needle	
Max. sewing speed		2000 s.p.m.	
Max.stitch length		5/16" (8 mm)	
Clearance under presser foot	by knee	5/8" (16 mm)	
	by hand	5/16" (8 mm)	
Needle bar stroke		1-29/64" (37 mm)	
Needle		DP x 17 (#23) , 135 x 17 (#160)	DP x 17 (#25) , 135 x 17 (#200)
Thread		#20 - #5 (standard #8)	lower #5, upper #0 (standard)
Hook		Large horizontal axis hook (2.0 times)	Large horizontal axis hook (2.0 times) (For thick thread)
Amount of lift of walking foot		5/64"-3/16" (standard 9/64") [2 - 5 mm (standard 3.5 mm)]	
Thread take up lever		Link type	
Lubrication		Automatic lubrication type (there is some exception)	
Bed size		18-45/64" x 7" (475 x 178 mm)	
Bobbin size		Φ 1-1/64" (Φ 25.8 mm), t=27/67"(10.8mm)	
Working space		10-15/64" x 4-23/32" (260 x 120 mm)	
Net weight(Head only)		29Kg	

NOTE: (1) Speed depends on threads, materials and type of operation
 (2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
 Chiba Prefecture, 273-0018, Japan
 Phone : +81-47-420-3561 (Overseas dept.)
 Fax : +81-47-420-3560
 E-mail : exsales@seiko-sewing.co.jp

Printed in Japan 2024. 7

<https://www.seiko-sewing.co.jp/en/>