



SAM-40

Two needle, Post bed, Large vertical axis hook, Multi different ornamental stitching, Automatic presser foot lift, Compound feed and walking, Lockstitch sewing machine



Variety

SAM-40

Standard model

Applications

- For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials
- Suitable for sewing such as automobile upholstery tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment and wearing apparel outdoor clothing.








Features

- Wide range of ornamental stitch
 - * 12 standard stitch patterns
 - * User designed stitch patterns can be registerd (Max.99 patterns)
- Easy operation of stitch pattern change by touch panel display
- Max.10mm stitch length



Stitch patterns



Touch panel display and 12 standard stitch patterns



Specifications

| Variety | | SAM-40 |
|-------------------------------------|--------------------------|--|
| Number of needle | | Two needle |
| Max. sewing speed | | 450 s.p.m. |
| Max.stitch length | | 25/64" (10 mm) |
| Clearance under presser foot | by hand | 23/64" (9 mm) |
| | by automatic foot lifter | 5/8" (16 mm) |
| Needle | bar stroke | 1-11/32" (34 mm) |
| Needle | | PF x 134KS #21 - #23 (Standerd #23) |
| Thread | | #20 - #1 (Standard #5) |
| Hook | | Large vertical axis hook (2.0 times) |
| Post height | | 7-1/64" (178 mm) |
| Thread take up lever | | Link type |
| Amount of walking foot movement | | 3/64" - 9/32" (1 - 7mm) |
| Walking foot movement change switch | | By touch panel display |
| Bobbin winder | | Built-in type located at the top of the sewing machine |
| Auto presser foot lifting device | | Pneumatic |
| Safety device | | Standard |
| Lubrication | | Semi-automatic lubrication type |
| Bed size | | 18-45/64" x 7-1/64" (475 x 178 mm) |
| Bobbin size | | Ф 1-9/64" (Ф 29 mm), t=1-31/64"(12.4 mm) |
| Working space | | 10-15/64" x 4-23/32" (260 x 120 mm) |

NOTE: (1) Speed depends on threads, materials and type of operation (2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi Chiba Prefecture, 273-0018, Japan

Phone: +81-47-420-3561 (Overseas dept.)
Fax: +81-47-420-3560

E-mail: exsales@seiko-sewing.co.jp

https://www.seiko-sewing.co.jp/en/

Printed in Japan 2024. 7