

# TE series

Single needle, Cylinder bed, Oscillating shuttle hook, Lower feed, Lockstitch machines



## Variety

**TE-6**  
Standard model

**TE-6B**  
Reverse stitch

## Applications

- For sewing light to medium heavy weight materials such as leather, vinyl, bags, pouches, various sports equipments and other curved work.



## Features

- Standard is narrow toe presser foot and roller foot is supplied as accessories.
- Suitable for sewing of high-class products, due to the feature of the oscillating hook, which ensures perfect seam tightness.
- Cam take-up.
- Reverse stitching by stitch adjusting lever. (**TE-6B**)
- Long beak oscillating shuttle hook.
- Cloth plate for flat work available at extra charge. (Part no. 8136C)



Long beak oscillating shuttle hook



Cloth plate for flat work

## Specifications

Variety		TE-6	TE-6B
Number of needle		Single needle	
Max. sewing speed		1,400 s.p.m.	
Max. stitch length		15/64" (6 mm)	13/64" (4.5 mm)
Clearance under presser foot	by knee	25/64" (10 mm)	
	by hand	9/32" (7 mm)	
Needle bar stroke		1-27/64" (36 mm)	
Needle(standard)		DB x 1 (#19), 16 x 231 (#120)	
Thread (standard)		#20	
Hook		Long beak oscillating shuttle hook	
Presser foot	standard	Narrow toe	
	accessories	Roller	
Thread take up lever		Cam type	
Lubrication		Hand type	
Bobbin size		Φ 25/32" (Φ 20 mm), t=23/64"(9mm)	
Cylinder size		2-27/64" (61.5 mm) dia.	
Working space		11-1/32" x 5-5/16" (280 x 135 mm)	
Net weight(Head only)		18 Kg	

NOTE: (1) Speed depends on threads, materials and type of operation  
(2) Specifications subject to change without notice



**SEIKO SEWING MACHINE CO., LTD.**

2-13-6, Sakaecho, Funabashi-shi  
Chiba Prefecture, 273-0018, Japan

Phone : +81-47-420-3561 (Overseas dept.)

Fax : +81-47-420-3560

E-mail : exsales@seiko-sewing.co.jp

Printed in Japan 2024. 7

<https://www.seiko-sewing.co.jp/>